

**Statement of Evidence:**

**F361**

North Quarter Corner of Section 36, Township 37 North, Range 31 West, Watab Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.  
10" Blk Oak              N 15 W              352 links

1982 On July 15, 1982 William Lunser, LS 9394, found a 1/2" iron pipe and replaced it with a cast iron monument and filed a Certificate of Location (#173437). He notes a distance of 2660.29 feet to the NW Corner of Section 36.

2003 Surveying & Engineering Professionals found a CIM. They measured 2654.97 feet to the NE corner and 2660.44 feet to the NW corner of Section 36. Corner is 6.7 feet south 2.9 feet east of the lost position.

2004 County Coordinates obtained by GPS to CIM.  
NAD 83 (1996 Adjustment)  
N-137452.866  
E-475926.676

2008 Westwood Professional Services, Inc. found a cast iron monument at the intersection of fence lines north and west and a tree line east. Measured 2660.41 feet to the NW corner and 2655.00 feet to the NE corner of Section 36 which agrees with 1982 Lunser and 2003 Surveying & Engineering Professionals distances. CIM is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2004 position.