

Statement of Evidence:

F022

Northeast Corner of Section 2, Township 37 North, Range 31 West, Watab Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established the corner and set a wood post and bearing trees recorded:

10" Bur Oak	N 34 1/2 E	190 links
8" Bur Oak	N 35 1/2 W	253 links
16" Bur Oak	S 11 E	446 links

1923 County Surveyor's Record Book 1, page 315, notes a survey of Section 1 by Samuel S. Chute. An iron monument is noted at the corner location.

1936 M.B. Lang performed survey work as documented in Book 11 of Misc., Page 47 of Benton County records. He set judicial landmarks at the northeast, north sixteenth on the east line and east quarter corner of Section 2, measuring 2942.76 feet from the northeast to east quarter corners and 1605.34 feet from the northeast corner to the north sixteenth corner.

1978 Ronald Engelmeyer, LS 13334, found a 1½ " iron pipe and filed a Certificate of Location (#151565) and notes a distance of 2729.58 feet to the North ¼ corner of Sec. 1. This compares well with Chute's distance of 2732.0 feet.

2002 Westwood Professional Services, Inc. found a 1½" iron pipe, which fit the ties from 1978 certificate. Obtained GPS position.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-164395.826
E-473478.987

2009 The Benton County Surveyor's Office found the 1 1/2" iron pipe and the JLM at the north sixteenth on the east line of Section 2, measuring 1603.37 feet between them.