

**Statement of Evidence:**

**F052**

Northeast Corner of Section 5, Township 37 North, Range 31 West, Watab Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded:

10" Bur Oak	N 39 W	140 links
8" Bur Oak	S 56 1/2 W	118 links

1972 On August 25, 1972 William Lunser, LS 9394, set a RR spike at the centerline of County Road 55 and using the testimony of Mr. Graves (the landowner to the south). He filed a Certificate of Location (#133440) and notes a distance of 2677.29 feet to the North 1/4 Corner of Sec 4.

1985 On September 19, 1985 William Lunser notes a distance of 2700.61 feet to the North 1/4 Corner of Sec 5 (cast iron monument) per Doc. No. 191260.

1985 On October 4, 1985 William Lunser found a RR spike at the centerline of County Road 55 and replaced it with a cast iron monument and filed a Certificate of Location (#191261). He notes a distance of 2659.40 feet to the E 1/4 Corner of 32-38-31.

1990 MN/DNR survey information shows CIM found.

2002 Westwood Professional Services, Inc. found a CIM per Lunser's certificate.  
County Coordinates Obtained by GPS to CIM:  
NAD 83 (1996 Adjustment)  
N-164262.108  
E-457448.985

2004 MN/DOT  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-164262.159  
E-457448.966

2008 Westwood Professional Services, Inc. found a CIM at the corner location. CIM is accepted as marking the obliterated corner position. County Coordinates Obtained by GPS coincide with 2004 MN/DOT position.