

**Statement of Evidence:**

Northeast Corner of Section 11, Township 37 North, Range 31 West, Watab Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

14" Bur Oak S 73 E 245 links  
6" Bur Oak N 19 W 28 links

1923 County Surveyor's Record Book 1, page 333, shows a survey of Section 1 by Samuel S. Chute, which notes an iron monument at the corner location with the following reference tie:

Double Oak SE 132 feet

He measured 2674.84 feet to the East 1/4 corner of Section 2 (well point) and 2760.94 to North 1/4 corner of Section 12 (post).

No Date: County notes show iron pipe at the corner with the following reference ties.

24" Bur Oak SE 131.1  
14" Bur Oak N 158.7  
PP NE 36.15

1961-1968 M.W.Carley, LS 855, notes the following reference ties:

PP NE 36.44  
FP W 39.8  
FP SW 37.44

1978 Paul Wellen, LS 10461, found a 1/2" iron pipe on the centerline of a township road east and north. He filed a Certificate of Location (#151861).

1982 Paul Wellen's notes show a distance of 2763.79 feet to the North 1/4 corner of Section 12 and 2642.77 feet to the East 1/4 corner of Section 11.

2005 Daniel Kron, LS 42621, found 1 1/2" iron pipe and measured 2661.97 feet to the East 1/4 corner Sec. 2 and 2764.82 feet to the North 1/4 corner Sec. 12. Distances seem to confirm that the iron found is the same as set in the 1923 survey.

County Coordinates obtained by SEPI:

NAD 83 (1996 Adjustment)  
N- 158794.005  
E- 473404.032