

Statement of Evidence:

F122

Northeast Corner of Section 12, Township 37 North, Range 31 West, Watab Township,
4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

4" Blk. Oak	N 66 1/2 E	291 links
4" Blk. Oak	N 43 1/2 W	69 links
6" Blk. Oak	S 4 1/2 W	330 links
6" Bur Oak	S 83 1/2 E	182 links

1923 County Surveyor's Record Book 1, page 315, shows survey of Section 1 by Samuel S. Chute that notes a sawed 4"X4" oak post at the corner location. Gives distances of 2760.94 feet to the post at the North 1/4 corner of Section 12 and 2656.75 feet to the post at the East 1/4 corner of Section 1.

1940 County Engineer's Notebook No. 133 contains a road survey for CAR No. 41 running south to north. Corner is shown as a rock in 4-way road intersection. Ties:

TP	E	31.0
12" Oak	NW	74.25

1961 County Surveyor's Record Book 1, page 335, shows found rock and placed an iron over the rock with the following reference ties.

PP	NW	48.6
TP	SE	48.13
TP	NE	38.4

(Notes in Notebook 133.)

1980 William Lunser, LS 9394, found a 3/4" iron pin at the intersection of roads north/south/west and a field line east. He left it as found and filed a Certificate of Location (#158865). He notes a distance of 2739.05 feet to the East 1/4 corner of Section 12. (Note: tie to PP NW is 48.43' that checks with 1961 tie.)

1982 Paul Wellen, LS 10461, measured 2739.03 feet to the East 1/4 corner of Section 12 and 2764.25 feet to the North 1/4 corner of Section 12.

1990 County Highway notes call for a RR spike at the corner location.

2002 Westwood Professional Services, Inc. found a RR Spike at the centerline of 105th Street NE (from the east) and 1.5 feet east of the centerline of County Road 78) running north and south. Appears RR spike is probably over rock, but **needs to be pulled and checked for rock and also check for old ties.**

2005 Daniel Kron, LS 42621, found RR spike.
County Coordinates obtained by SEPI:
NAD 83 (1996 Adjustment)
N- 158995.539
E- 478929.428

Benton County Surveyor's Office
Jerome C. Wittstock, County Surveyor
Minnesota License No. 19552

2007 Westwood Professional Services, Inc. found a RR Spike at the centerline of 105th Street NE (from the east) and 1.5 feet east of the centerline of County Road 78) running north and south. RR spike was removed and an excavation revealed a $\frac{3}{4}$ " pipe over a stone as previously noted. Stone was left as found and a cast iron monument was placed and new ties measured and noted.

County Coordinates obtained by GPS:

NAD 83 (1996 Adjustment)
N- 158995.539
E- 478929.428