

**Statement of Evidence:**

Northeast Corner of Section 14, Township 37 North, Range 31 West, Watab Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Burr Oak S 17 1/2 W	154 links
14" Burr Oak N 44 1/2 E	163 links

1932 County Engineer's notebook No. 73 contains a road survey for S. A. R. 13 by H. G. Elletson. Corner is noted as a POT in center of east-west road and on line with town road (not graded) south and fence north.

1959 County Highway plans show same stationing as in 1932 with corner 3.1 feet east, with fence south and field entrance north.

1982 David Regan, LS 12236, found a RR spike in the centerline of County Road 13 (running east and west) and a fence line from the north. He removed the RR spike and set a cast iron monument and filed a Certificate of Location (#163363).

1985 William Lunser, LS 9394, notes that the distance between the East 1/4 corner of Section 14, a cast iron monument, and the NE corner is 2722.94 feet, per Certificate of Location (#173434).

2002 Westwood Professional Services, Inc.  
County Coordinates obtained by GPS (Cast Iron Monument)  
NAD 83 (1996 Adjustment)  
N-153507.960  
E-473529.539

***NOTE: CORNER NEEDS FURTHER ANALYSIS.***

Westwood Professional Services, Inc. measured:

2812.11 feet to the North 1/4 corner Section 14.

2723.07 feet to the East 1/4 corner Section 14.

Wellen (1989) measured 2658.72 feet to the North 1/4 corner Section 13.

Milner Carley measured 2647.50 feet to the East 1/4 corner Section 11.

2004 MN/DOT  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-153507.924  
E-473529.528