

**Statement of Evidence:**

**F162**

Northeast Corner of Section 16, Township 37 North, Range 31 West, Watab Township,  
4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post in a mound for the corner location.

1916 County Surveyor's Record Book 1, page 313, and Record Book A, Map No. 20), shows a survey by J.P. Soderstrum, which notes an old oak post at the corner location in the intersection of the centerline of roads. He set 2 large rocks on top of each other and notes a distance of 40.71 chains (2686.86 feet) to the North  $\frac{1}{4}$  corner of Sec 15. Tie:  
SW Cor School Hse NE 249 links (164.34 feet)

No Date County Surveyor's Record Book 1, page 343, notes a stone at the corner with same tie.

1982 David Regan, LS 12236, found a 1" pipe over a stone in the centerline of roads east/west and north/south. He set a cast iron monument over the stone and removed the 1" pipe and filed a Certificate of Location (#162600). Lists tie of 142.10 feet NE to SW corner of garage.

2003 Surveying & Engineering Professionals, Inc reported finding a CIM.

2004 MN/DOT  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-153437.714  
E-462794.998

2008 Westwood Professional Services, Inc. found a CIM at the corner location fitting two of Regan's 1982 ties and coordinates obtained by GPS coincide with 2004 MN/DOT position. CIM is accepted as marking the obliterated position for this corner.