

Statement of Evidence:

F332

Northeast Corner of Section 33, Township 37 North, Range 31 West, Watab Township,
4th Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office surveyor, John Ryan, set a wood post at this location and bearing trees were recorded.

20" Bur Oak	N 33 E	447 links
12" Bur Oak	S 86 E	430 links

Corner is also noted as a meander corner on the east bank of the Mississippi River.

NOTE: In the early 1900's the Sartell dam was built, which flooded the corner area.

1963 Arthur Miller, LS, surveyed the plat of SHOREWOOD PARK in Section 27. The plat shows iron monuments along the south line of Section 27.

1982 William Lunser, LS 9394, found a 1/2" iron pipe. He replaced it with a cast iron monument and filed a Certificate of Location (#173436) calling the corner a Meander Corner. Monument is 2366.34 feet west of the North 1/4 corner of Section 34.

1999 James Kramer, LS 23668, found a cast iron monument and some of Lunsers ties. He filed a Certificate of Location (#265881), accepting the corner as a witness to the section line (not a meander corner). CIM was found to be 2364.03 feet west of the North 1/4 corner. The actual section corner position is computed at 2640.00 feet west of the CIM and on its extension from the North 1/4 corner, placing it at 275.97 feet west.

MN/DOT survey information gives coordinates to witness monument:

N- 137351.592
E- 462923.772

2003 Westwood Professional Services, Inc. found CIM. Measured 2364.43 feet to the North 1/4 corner of Section 34. Determine position for section corner at 2640.00 feet west of the North 1/4 corner Section 34 on the extension of the line through the CIM placing it at 275.57 feet west.

County Coordinates obtained by GPS to CIM reference.

NAD 83 (1996 Adjustment)
N- 137351.941
E- 462923.270