

Statement of Evidence:

E011

The North Quarter Corner of Section 1, Township 38 North, Range 32 West, West Langola Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post at this location and bearing trees were recorded.

4" Blk Oak	S 42 1/2 W	244 links
2" Blk Oak	N 76 1/4 E	437 links

A line tree is noted 12" Bur Oak, West 24.34 chains

1979 Carley Engineering established this corner and set a 1/2" iron pipe at the corner location, while doing a subdivision of Section 36-39-32.

1982 David Regan, LS 12236, found a 1/2" iron pipe and set a cast iron monument in its place. He found no resurvey information in the Benton or Morrison County records on this corner. He replaced the iron pipe with a County cast iron monument.

1988 On July 14, 1988 Paul Wollen, LS 10461, found a cast iron monument and filed a Certificate of Location (#191233).

2002 On June 5, 2002 Westwood Professional Services, Inc. found a broken off cast iron monument. We measured 5433.61 feet between section corners and found the 1/4 corner to be 18.77 feet east of the lost position.
County Coordinates (Broken CIM) by GPS
NAD 83 (1996 Adjustment)
N- 196201.492
E- 443324.204