

**Statement of Evidence:**

**E133**

East Quarter Corner of Section 13, Township 38 North, Range 32 West, West Langola Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office survey set a wood post in a mound at the corner location with a pit 6 links north.
- 1991 David Regan, LS 12236, set a 3/4" iron monument at the centerline of a County Road north/south and filed a Certificate of Location (#223473).
- 2001 Westwood Professional Services, Inc. found a 3/4" iron pipe flush at the intersection of County Road 73 (running north and south) and occupations lines (from the east and west).
- 2002 No resurvey information was found on this corner in the Benton County records.  
Westwood Professional Services, Inc. found a 3/4" open.  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-182839.062  
E-446421.412
- 2004 MN/DOT  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-182839.041  
E-446421.403
- 2008 Westwood Professional Services, Inc. found a 3/4" iron pipe in the centerline of 45<sup>th</sup> Ave NW 0.26' from lost position. 3/4" iron pipe is accepted as marking the obliterated location for this corner. County Coordinates obtained by GPS coincide with 2004 MN/DOT position.