

Statement of Evidence:

E043

The East Quarter Corner of Section 4, Township 38 North, Range 32 West, West Langola Township, 4th Principal Meridian, Benton County, Minnesota.

- 1852 Original US General Land Office surveyor, Edwin James Jr., set a wood post at this location and bearing trees were recorded.

| | | |
|------------|------------|-----------|
| 6" Bur Oak | N 12 1/2 W | 13 links |
| 8" Bur Oak | S 60 1/2 E | 200 links |

- 1879 County Surveyor's Record Book 2, page 1, contains a road survey by Richard Cronk that shows road at this 1/4 post running east-west.

- 1979 On October 12, 1979 Paul Wellen, LS 10461, set a cast iron monument at the intersection of the centerline of an east/west road, a road from the north and a fence line from the south. A Certificate of Location (#155144) was filed. It is noted on said document that the E 1/4 corner is 5286.24 feet east of the W 1/4 corner.

- 2002 On June 6, 2002 Westwood Professional Services, Inc. found a cast iron monument and 1 previous tie at the intersection of the centerlines of 75th Avenue NW (running north) and Acorn Road NW (running east and west). No evidence of GLO BT's.
County Coordinates obtained by GPS (Cast Iron Monument)
NAD 83 (1996 Adjustment)
N-193447.133
E-430008.039

- 2008 Westwood Professional Services, Inc. found a cast iron monument at the intersection of the centerlines of 75th Avenue NW (running north) and Acorn Road NW (running east and west). No evidence of GLO BT's.
County Coordinates obtained by GPS coincide with 2002 location. Ties are shown on the front of this certificate.