

**Statement of Evidence:**

**E013**

The East Quarter Corner of Section 1, Township 38 North, Range 32 West, West Langola Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post at this location and bearing trees were recorded.

6" Blk Oak	2 1/2 W	240 links
6" Blk Oak	S 43 E	286 links

A line tree is noted as a 6" Blk Oak, North, 18.31 chains.

1982 Paul Wellen's, LS 10461, survey notes show corner 6 feet west of centerline of north-south road with ties:

R.H. in 10" Poplar	NE	28.73
N&D in 3" Oak	E	16.06
R.H. in 6" Poplar	SE	22.21

He measured 2687.36 feet to the SE corner of Section 1.

1988 Bruce Skipton, LS 17768, found a 3/4" iron pipe at the corner location. No resurvey information was found in the Benton County records. On October 17, 1988 he set a cast iron monument over the iron pipe and filed a Certificate of Location (#191235).

2002 On January 24, 2002 Westwood Professional Services, Inc. found a cast iron monument down 1 foot.

County Coordinates obtained by GPS to CIM:

NAD 83 (1996 Adjustment)  
N- 193580.775  
E- 446097.112

2008 Westwood Professional Services, Inc. found a cast iron monument 4' east of the north/south centerline. Coordinates obtained by RTK GPS coincide with 2002 position.