

**Statement of Evidence:**

**E252**

Northeast Corner of Section 25, Township 38 North, Range 32 West, West Langola Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office survey set a wood post in a mound with a pit 6 links north for the corner location.
- 1967 Carley Engineering set an iron monument at the corner for a survey done in Section 24.
- 1991 David Regan, LS 12236, set an iron monument on the centerline of a north/south county road and a township road east and according to the Carley survey.
- 2001 Westwood Professional Services, Inc. found a 1/2" open at the intersection of the centerlines of 135<sup>th</sup> Street NW (running east and west) and County Road 73 (running north and south).
- 2002 Westwood Professional Services, Inc. found 1/2" open.  
County Coordinates obtained by GPS (1/2" open)  
NAD 83 (1996 Adjustment)  
N-174760.973  
E-446652.637
- 2004 MN/DOT  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-174760.961  
E-446652.684
- 2008 Westwood Professional Services, Inc. found a 1/2" iron pipe at the intersection of County Road No. 73 and a Township Road to the east. Iron pipe is ~6.4 feet NW of the lost position for this corner but fits longstanding road occupation. The 1/2" iron pipe is accepted as marking the obliterated location for this corner. County Coordinates obtained by GPS coincide with 2004 MN/DOT position.