

Statement of Evidence:

E122

The Northeast Corner of Section 12, Township 38 North, Range 32 West, West Langola Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post at this location and bearing trees were recorded.

8" Bur Oak	N 47 1/2 E	80 links
6" Blk Oak	N 62 1/2 W	20 links
8" Blk Oak	S 45 1/2 W	49 links
8" Bur Oak	S 66 E	49 links

1941 County Surveyor's Record Book 2, page 98 contains a survey by HG Elleston of Section 7, 38-31. Survey shows this corner but does not give any information about a monument.

1978 Paul Wellen's, LS 10461, notes, per Book 11, page 32, a distance of 2745.64 feet to the North 1/4 corner Sec. 12 and a distance of 2809.47 feet to the East 1/4 corner Sec. 12.

1982 Paul Wellen notes, per Wellen's Book 31, page 40, a distance of 2687.36 feet to the East 1/4 corner Sec. 1.

1988 Bruce Skipton, LS 17768, found a 1/2" pipe. He set a cast iron monument and filed a Certificate of Location (#191236).

2003 Westwood Professional Services, Inc. located a cast iron monument using GPS.
County Coordinates Obtained by GPS (Cast Iron Monument)
NAD 83 (1996 Adjustment)
N-190896.497
E-446163.803

2008 Westwood Professional Services, Inc. located a cast iron monument. County Surveyor's Record Book 2, page 98 contains a survey by HG Elleston of Section 7- 38-31. Survey gives a distance of 5369.0 feet for the west line of Section 7. Westwood finds CIM to measure 5369.33 feet north of the SE corner and accepts CIM as marking the obliterated position.
County Coordinates Obtained by GPS (Cast Iron Monument)
NAD 83 (1996 Adjustment)
N-190896.497
E-446163.803