

Statement of Evidence:

E052

The Northeast Corner of Section 5, Township 38 North, Range 32 West, West Langola Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office survey established this corner and set a wood post for the corner location with the following bearing trees marked:

12" Bur Oak	N 21 E	18 links
12" Bur Oak	S 86 1/2 W	18 links

A line tree is noted 8" Bur Oak, East, 25.00 chains

- 1991 Tom Thiessen (RLS No.16097) set a cast iron monument at the intersection of fence lines from the north/east/west. He looked for and found no evidence of a corner monument and accepted the fence corner as an obliterated position. A Certificate of Location (#336349) was filed in Morrison County.

- 1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N-196044.487
E-424411.572

- 2002 No resurvey information was found on this corner in the Benton County records.

- 2006 Neither the original government corner post nor bearing or line trees were found. Westwood Professional Services, Inc. found a CIM at the intersection of fences east, west, and north per Document Number 336349. This corner location fits the original GLO distance east within 14 feet assuming two 2-pole busts. Several half-miles along the north County line measure approximately 33 or 66 feet (2 or 4 poles) long of 2640. I accepted the CIM as marking the obliterated position and obtained updated coordinates.

County Coordinates
NAD 83 (1996 Adjustment)
N- 196044.929
E- 424410.826