

Statement of Evidence:

E042

The Northeast Corner of Section 4, Township 38 North, Range 32 West, West Langola Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established this corner and set a wood post for the corner location with the following bearing trees marked:

6" Bur Oak	N 22 E	60 links
10" Bur Oak	S 59 W	126 links
6" Bur Oak	S 69 E	88 links

1986 Document No. 308438 in Morrison County is a Certificate of Location for this corner by Thomas Thiesen, LS 16097, showing the corner re-established by obliterated means after excavating and finding no evidence of the corner. A cast iron monument was set.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N-196120.878
E-429833.148

2002 On June 6, 2002 Westwood Professional Services, Inc. found a 1/2" iron with an unknown cap number at the centerline of a north/south road and +/- 20 feet north of a power pole line. We found 2 ties from the 1986 certificate that fit the iron found.

2006 Neither the original government corner post nor bearing or line trees were found. Westwood Professional Services, Inc. found a 1/2" iron pipe capped 22072 in the centerline of the north-south road and 20 feet north of a power line. This corner location fits the original GLO distance west within 4 feet assuming two 2-pole busts and within a half foot to the east again assuming two 2-pole busts. Several half-miles along the north County line measure approximately 33 or 66 feet (2 or 4 poles) long of 2640. I accepted the 1/2" iron pipe as marking the obliterated position and obtained updated coordinates.

County Coordinates
NAD 83 (1996 Adjustment)
N- 196121.234
E- 429832.303