

Statement of Evidence:

E131

North Quarter Corner of Section 13, Township 38 North, Range 32 West, West Langola Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a post in a mound at the corner location and a pit 8 links east.

1991 David Regan, LS 12236, set an iron monument on the extension of the centerline of a road west and a fence line from the north, which is 2' north of the north edge of the bit. A Certificate of Location (#223474) was filed.

2002 Westwood Professional Services, Inc. found an iron pipe capped #12236 and located it using GPS.
County Coordinates (#12236)
NAD 83 (1996 Adjustment)
N-185526.744
E-443619.616

2003 Certificate of Survey by Kurt Kisch, LS 23968, shows corner marked by an iron pipe with cap No. 17768. Distance checks to NE corner as obtained by Westwood Professional Services, Inc.

2004 MN/DOT
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-185526.719
E-443619.638

2008 Westwood Professional Services, Inc. found 1/2" iron pipe and located it using GPS. Iron Pipe falls ~3 feet from lost position which supports Regan's method of using longstanding occupation as evidence. Accepted iron pipe as marking the obliterated position. Verified 2004 MN/DOT coordinates.