

**Statement of Evidence:**

**E091**

The North Quarter Corner of Section 9, Township 38 North, Range 32 West, West Langola Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office surveyor, Edwin James Jr. set a wood post at this location and bearing trees were recorded.

14" Bur Oak	N 69 E	57 links
18" Bur Oak	N 85 W	105 links

1979 On October 12, 1979 Paul Wellen, LS 10461, set a cast iron monument at the intersection of fence lines from the east/west/north. A Certificate of Location (#155146) was filed that shows corner 942.03 feet east of the meander corner.

1999 Paul Wellen's records show the CIM was found and distance of 2641.64 feet was measured to the NE corner of Section 9.

2000 On August 13, 2000 Westwood Professional Services, Inc. looked for said corner and found no indication of an iron at the occupation lines.

2008 Westwood Professional Services, Inc. found a CIM at fence intersections east, west and north. CIM measures 2641.59 feet west of the NE corner of Section 9 (2640 GLO) and 891.64 feet east of the MC on the north line of Section 9 (891 GLO). CIM is ~3 feet north of straight line from NE corner of Section 9 and MC. Fence line occupation is longstanding evidence of section lines. CIM is accepted as marking the obliterated position.  
County Coordinates obtained with GPS  
NAD 83 (1996 Adjustment)  
N- 190740.920  
E- 427398.930