

Statement of Evidence:

E041

The North Quarter Corner of Section 4, Township 38 North, Range 32 West, West Langola Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post in a mound with a pit 6 links east for the corner location.
A line tree is noted as an 8" Bur Oak, West, 15.00 chains
- 1979 On October 12, 1979 Paul Wellen, LS 10461, found a 3/4" iron pipe at the intersection of a tree/fence line east/west and a tree/fence line north. He set a cast iron monument and filed a Certificate of Location (#155142). This corner is 5352.84 feet north of the S 1/4 corner of Section 4.
- 1999 Paul Wellens' records show a CIM found with distances of 2720.01 feet to the NW corner and 2702.10 feet to the NE corner of Section 4.
- 2006 At this location neither the original GLO corner post nor bearing or line trees were found. Westwood Professional Services, Inc. found a CIM at the intersection of fences east, west, and north per document number 155142. This corner location fits the original GLO distance west within 14 feet assuming two 2-pole busts and east within 4 feet assuming two 2-pole busts. Several half-miles along the north County line measure approximately 33 or 66 feet (2 or 4 poles) long of 2640. I accepted the CIM as marking the obliterated position and obtained updated coordinates.

County Coordinates
NAD 83 (1996 Adjustment)
N- 196087.053
E- 427130.422