

**Statement of Evidence:**

**K322**

The Northeast Corner of Section 32, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees:

15" Bur Oak	S 1 1/2 E	693 links
12" Bur Oak	S 1 3/4 W	661 links

Undated County Surveyor's Record Book 1, page 147, notes a stone with the following reference ties:

6" W Oak	W	54.8
14" R Oak	SE	67.3

1982 David Regan, LS 12236, set a cast iron monument at the centerline of a road north/south and a fence line west. He filed a Certificate of Location (#163372).

2003 On 5/7/03 dug with a backhoe at corner area and found a 8" x 10" x 16" pointed stone standing upright down 2.2 feet under the east side of the CIM set in 1982. Found no evidence of the previous ties noted as "undated". Left CIM in place as the corner and took new ties:

N & D in north side 18" Bur Oak	East	76.29
N & D in NW side PP	SE	61.64
Iron pipe w/cap 16095	East	33.00

County Coordinates Obtained by GPS to CIM:

NAD 83 (1996 Adjustment)  
N- 105599.290  
E- 521665.614

2008 The County Surveyor's Office searched and found a cast iron monument as set by Regan in 1982 and verified per corner excavation of found stone monument in 2003. The Surveyor accepts the CIM position and set new ties to same. Benton Coordinates obtained by GPS to the CIM agree with those reported in 2003, above.