

Statement of Evidence:

K142

The Northeast Corner of Section 14, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Blk Oak	N 54 E	38 links
12" Blk Oak	N 38 1/2 W	24 links

1933 County Engineer's Notebook No. 67 shows road survey by H. G. Elletson running east-west. Corner is shown as a stone monument with ties:

8" Oak	NE	49.6'
10" Oak	SE	80.6'

1940 County Engineer's Notebook No. 134 contains survey of CAR 40 running south to north on section line and terminating at this corner. Corner is shown as a spike set in center of CAR 30. Ties same as 1933.

1963 County Surveyor's Record Book 1, page 109, calls for an iron at the corner with the following reference ties.

16" R Oak	NE	50.0
PP	NW	49.35

(Entry in notebook No. 67 shows found spike and set iron with these ties.)
Older record also refers to stone and shows same ties as in 1933.

1982 David Regan, LS 12236, found a 1/2" solid pin at the P.I. of CR 50 and centerline of CR 64 south. He set a cast iron monument over the pin and filed a Certificate of Location (#163367).

2001 Westwood Professional Services, Inc. found a cast iron monument at the intersections of County Road 64 (running south) and County Road 50 (running east and west).

2002 County Coordinates Obtained by GPS to CIM:
NAD 83 (1996 Adjustment)
N-122118.30
E-537485.71

Note: Based on survey record for East 1/4 corner, stone probably was set by Soderstrum in 1914.

NOTE: Corner location is probably good based on perpetuation of the position by the County Highway Department, but should be excavated to search for stone.