

**Statement of Evidence:**

**K102**

Northeast Corner of Section 10, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees:

10" Bur Oak	N 64 E	34 links
14" Aspen	S 19 1/2 W	17 links

A line tree was noted as a 11" Elm West 17.80 chains.

1929 County Surveyor's Record Book 1, page 89, and Record Book A, Map No. 50, shows H.G. Elletson surveyed Section 3, doing a complete section subdivision with all 1/16<sup>th</sup> corners set. The survey notes an iron monument with the following reference ties:

Twin Elm	North	42.8
TP	SW	79.6

He notes a distance of 2627.8 feet to the North 1/4 corner Sec 10 and a distance of 2589.4 feet to the East 1/4 corner Sec 3. (Notes in Notebook 48)

1977 Paul Wollen, LS 10461, set a 1" steel pin at the centerline of an east/west road. He filed a Certificate of Location (#147245).

2004 Found 1" iron pin in center of east-west road.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 127171.809

E- 532085.592

2008 The County Surveyors Office searched and found a 1" steel pin approximately 0.5' below the surface of the east-west gravel road (45<sup>th</sup> Street N.E.). Position agrees with 1929 distances (2629.96 ft. & 2588.08 ft vs. 2627.8 ft. & 2589.4 ft.). The Surveyor accepts the monument as marking the obliterated position and set new ties.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 127171.885

E- 532085.597