

Benton County Surveyor's Office  
Jerome C. Wittstock, County Surveyor  
Minnesota License No. 19552

**Statement of Evidence:**

**K042**

The Northeast Corner of Section 4, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original General Land Office survey established this corner set a wood post at this location and bearing trees were recorded.

12" W Ash	N 33 E	5 links
8" W Ash	N 70 W	37 links
14" W Ash	S 89 W	31 links
20" W Ash	S 38 E	48 links

1929 County Surveyor's Record Book 1, page 89 and Record Book A, Map No. 50 shows H.G. Elletson surveyed Section 3, doing a complete section subdivision with all 1/16<sup>th</sup> corners set. The survey notes an iron monument at the corner with ties:

12" Elm	West	64.8
12" Elm	NW	34.0

(Notes in Notebook 48)

1931 County Engineer's notebook No. 61 contains a road survey running south from this corner. Corner marked by an iron with same ties as 1929.

1940's MN/DOT alignment map for TH 23 shows an iron pin at this corner 2300.9 feet south of centerline.

1949 County Highway notebook 1, page 66 contains ties to a found 2" angle iron by rotted off fence post. Ties:

MHD in 14" Oak	NW	42.0 feet
MHD in 8" Oak	SW	34.9 feet

1957 County Surveyor's Record Book 1, page 91, notes the following reference ties.

6" Ash	SE	47.35
20" Elm	SW	77.1
24" Elm	W	64.5

1960 County Surveyor's Record Book 1, page 91, notes the following reference ties.

14" W Oak	SW	128.9
15" Stump	SW	76.5
24" Elm	W	64.5

1972 Ronald Engelmeyer, LS 13334, found a 1" pin at the centerline of roads. He filed a Certificate of Location (#151556). He notes a 20" Elm WSW 64.5 feet and a 16" Oak SW 128.55 feet.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 132296.442
E- 526427.663

2001 Sam Deleo, LS 40341, found a cast iron monument at the centerline of roads north/south/east and a tree line west. He filed a Certificate of Location (Doc. No. 279106) and notes a distance of 2704.71 feet to the North 1/4 corner of Section 3. He notes a found dead and rotted tree down 64 feet west.

2003 County Coordinates obtained by GPS to CIM  
NAD 83 (1996 Adjustment)  
N- 132296.662  
E-526427.331

2009 Westwood Professional Services, Inc. placed a PK nail and Benton County washer over the found CIM. Reference ties and coordinates were verified.