

Statement of Evidence:

K331

North Quarter Corner of Section 33, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees:

6" Blk Oak	S 48 E	40 links
6" Blk Oak	N 89 1/2 W	13 links

1982 David Regan, LS 12236, set a cast iron monument at a centerline north/south road and a fence line east/west. He filed a Certificate of Location (#163373).

1993 William Lunser, LS 9394, set a cast iron monument at the centerline of roads north/south and a fence line east/west. The 1982 monument was destroyed as well as all but 1 tie due to road construction. He filed a Certificate of Location (#234172). He notes a distance of 2588.40 feet to the NW corner Sec 33 and a distance of 5208.38 feet to the South 1/4 corner Sec 33.

2003 Westwood Professional Services, Inc. found a CIM. Measured 2588.51 to the NW corner and 2642.93 feet to the NE corner.

2008 The County Surveyor's Office searched and found the CIM reported by Westwood Professional Services, Inc in 2003. The position fits ties to same by Lunser in 1992. The Surveyor accepts the position and updated ties.

County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 105580.479
E- 524253.992