

Statement of Evidence:

K181

The North Quarter Corner of Section 18, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established this corner set a wood post at this location and bearing trees were recorded.

5" Aspen	N 65 E	186 links
4" B. Oak	N 81 E	175 links

2001 Westwood Professional Services, Inc. found a pointed wood post, with top rotted off, lying flat, buried under a flat post, in a swampy area. The post falls on the extension of an old barbwire fence running west, a tree line running north, and an old trail running south.

Found a 20" Double Red Oak that fits the original GLO BT distance and bearing. Do not believe that the oak is the original BT, but believe it is highly likely that the current tree grew from the stump of the original BT. Accepted this corner as a perpetuated original corner. The position also fits the GLO notes that call for the corner being in a willow marsh. We removed the pointed wood post and set a cast iron monument in its place and established reference ties. By accepting this as the corner position creates a north/south quarter line that matches a fence corner at the center of the section. Other fence lines, throughout the section, meander back and forth as much as +/- 15 feet.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-121658.360

E-513815.975

2002 No resurvey information was found on this corner in the Benton County records.

2004 MN/DOT survey crew found CIM and obtained County Coordinates by GPS:

NAD 83 (1996 Adjustment)

N-121658.773

E-513815.983