

Statement of Evidence:

K171

North Quarter Corner of Section 17, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post was set and bearing trees were recorded

5" Aspen	S 19 E	35 links
5" Aspen	N 48 1/2 E	10 links

2001 Westwood Professional Services, Inc. found a steel post (fence corner) set in concrete. We looked for other evidence of monuments and found nothing. We measured 5153.41 feet between section corners and found the steel post to be 6.5 feet south and 6.6 feet east of the lost position. We accepted the post as marking the obliterated location of the corner. We established reference ties using the top of the fence post.

Nail and Disc in E face 6" Elm up 3.5	SE	6.81
Nail and Disc in E face 6" Elm up 3.5	S	23.01
Nail and Disc in 1 st 8" diameter FP	W	16.05

County Coordinates Obtained by GPS (for reference use only – 3rd order)

NAD 83 (1996 Adjustment)

N-121732.731

E-519066.029

2002 No record history found on this corner in the Benton County records.

2003 Certificate of Location filed as Document No. 295387.

2004 MN/DOT found steel fence post.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-121732.609

E-519065.736