

**Statement of Evidence:**

**K151**

North Quarter Corner of Section 15, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees:

5" Blk Ash	N 2 W	36 links
7" Aspen	S 46 1/2 E	23 links

1933 County Engineer's Notebook No. 67 shows road survey by H. G. Elletson running east-west. Corner is shown as a spike set in center of road with fence north and ties:

Stake North 28.0'

Stationing gives distances of 2662.6 feet to the NE corner and 2646.6 feet to the NW corner with no delta angle. (Also noted in County Surveyor's Record Book 1, page 113.)

1962 Entry in same notebook shows found spike with ties:

PP	N	34.95'
TP	SE	88.65'

1984 Dave Regan, LS 12236, set a 1/2" pipe in the centerline of roads east/west and a field division line north/south. He filed a Certificate of Location (#173412) and notes a distance of 2661.07 feet to the NE corner Sec 15.

2004 Found 1/2 " iron pipe in east-west road. Measured 2661.07 feet to the NE corner and 2651.20 feet to the NW corner. Pipe is 0.3 feet south of a straight line between section corners.

2008 The County Surveyor's Office searched and found a 1/2" iron pipe on the centerline of bituminous road (County Road No. 50). Position agrees with 1962 tie to power pole, and 1933 distance to NE corner (2661.1 ft. vs. 2662.6 ft.). Surveyor accepts the position as marking the obliterated corner. Ties were updated.

County Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 121847.479  
E- 529518.618