

Statement of Evidence:

K081

North Quarter Corner of Section 8, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established this corner set a wood post at this location and bearing trees were recorded.
12" W Oak S 4 E 71 links

1913? County Surveyor's Record Book 1, pages 34 & 35, contains a survey of Section 5 by County Surveyor, J. A. Stanton, which notes this corner found as marked by an iron rod set by former County Surveyor.

2003 Survey information from Brown Herkenhoff gives a distance of 5217.64 feet for the north line of Section 8.

2004 MN/DOT found spike and pulled and found nothing else. Set CIM. Measured 2587.73 feet to the NW corner and 2628.82 feet to the NE corner.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-126970.316
E- 518886.503

2008 Westwood Professional Services, Inc. found a CIM and confirms 2004 MN/DOT coordinate position by RTK GPS. Made extensive search for iron rod set in ~1913 and nothing was found. Position fits favorably with center of section and sixteenth occupation lines to the north in Section 5 as well as center of section and sixteenth occupation lines to the south. CIM is accepted as marking the obliterated corner position. Ties are shown on the front of this certificate.