

**Statement of Evidence:**

**K031**

North Quarter Corner of Section 3, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original General Land Office survey established this corner and marked a 10" Ironwood for the corner. No bearing trees were recorded.  
A line tree was noted as a 10" W Oak West 17.72 chains.

Undated County Surveyor's Record Book 1, page 91, notes an iron at the corner.

1929 County Surveyor's Record Book 1, page 89, and County Surveyor's Record Book A, Map No. 50, is a survey of Section 3 by H. G. Elletson showing a complete section subdivision with all 1/16<sup>th</sup> corners set. Elletson notes an iron monument at the corner in center of road and a fence line north with the following reference ties.

|              |   |       |
|--------------|---|-------|
| 12" Basswood | S | 108.8 |
| Fen Cor      | N | 18.6  |

He notes a distance of 2703.2 feet to the NE corner Sec. 4 and a distance of 2635.2 feet to the NE corner Sec. 3. (Notes in Notebook 48)

1986 Phil Daubanton, County Highway Dept., found a 1/2" X 3' long bent pipe. He replaced it with a 3/4" pipe and a RR Spike at the centerline of roads east/west and a fence line north with the following reference ties.

|                         |    |        |
|-------------------------|----|--------|
| 'X' in large field rock | SE | 47.07  |
| E end CMP               | SW | 65.51  |
| W end CMP               | SW | 102.65 |

1997 Sidney Williamson, LS 10918, gives distances on Certificate of Location for the NE corner Sec. 3 of 2709.8 feet to the NW corner and 2637.43 to the NE corner of Section 3.

2001 Sam Deleo, LS 40341, found a RR Spike over a 1 1/4" X 20" Iron Pipe and replaced it with a cast iron monument. He filed a Certificate of Location (Doc. No. 279109) and notes a distance of 2637.50 feet to the NE corner Sec. 3 and a distance of 2704.71 feet to the NE corner Sec. 4.

2004 Westwood Professional Services, Inc. found CIM. Measured 2637.64 feet to the NE corner and 2704.66 feet to the NW corner.  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 132318.173  
E- 529131.907