

Statement of Evidence:

K333

East Quarter Corner of Section 33, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

9" Bur Oak S 67 1/2 W 832 links

Pre 1940 MN/DOT notes by C. H. West for TH 95 show corner assumed at intersection of fence lines east, west and south.

1990 William Lunser, LS 9394, set a 1/2" pipe at the intersection of fence line north/south/east. He filed Certificate of Location (#234174). He notes a distance of 2719.96 feet to the NE corner Sec 33 and a distance of 5245.11 feet to the East 1/4 corner Sec 34 and a distance of 2643.30 feet to the SE Cor Sec 33.

1995 Record plat of STONY BROOK ESTATES by William Lunser, LS 9394, shows corner as an iron pipe.

2005 WSN found 1/2" iron pipe per Lunser's Certificate. Measured 2721.08 feet to the NE corner and 2642.48 feet to the SE corner.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 102878.804

E- 526944.494

This corner is noted on the following recorded plats

<i>EAGLE VIEW COMMONS</i>	8/16/1998	William Lunser
<i>STONY BROOK ESTATES</i>	5/25/1995	William Lunser

2008 Westwood Professional Services, Inc. found a 1/2" iron pipe at the intersection of fences east/west/south. Measured 2721.08 feet to the NE corner and 2642.48 feet to the SE corner of Section 33 and measured 5245.11 feet to the E1/4 of Section 34. These measurements agree with 1990 Lunser and 2005 WSN distances. 1/2" iron pipe is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2005 WSN position.