

Statement of Evidence:

K313

The East Quarter Corner of Section 31, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees:

12" Tamarac	N 30 W	71 links
10" Blk Ash	N 83 E	34 links

1930 County Surveyor's Record Book 1, page 145, contains a survey by H. G. Elletson which shows a post set at the lost position measuring 5475.4 feet for the mile with the following reference ties:

14" Elm	NE	9.0
8" Ash	S	28.0

(Notes in County Engineer's notebook 79)

Pre 1940 MN/DOT notes by C. H. West for TH 95 show corner being a blazed stake in place being 2.0 feet north of proposed centerline.

2009 Westwood Professional Services, Inc. located a fence intersection of fences north, south, east and west in a wooded area. The fence intersection falls 2 feet north and 20 feet east of the lost position. Believing the long-standing fences to be the best available evidence of the obliterated position, a 1/2-inch by 15-inch iron pipe capped 19552 was set on the south side of the corner fence post, reference ties established and coordinates were obtained by traverse.

Coordinates Obtained by Traverse

NAD 83 (1996 Adjustment)

N-102839.829

E-516377.937