

Statement of Evidence:

K283

The East Quarter Corner of Section 28, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees:

6" Blk Oak	S 7 3/4 W	96 links
5" Blk Oak	S 62 1/2 W	91 links

1931 County Engineer's notebook 61 contains road survey that shows a spike at the corner in north-south road and fence line west with ties:

F.P.	NE	28.2'
F.P.	SE	32.3'

Stationing gives distances of 2709.60 feet to the NE corner and 2673.9 feet to the SE corner with a delta angle of 0-30 left (running north to south).

1979 County Highway notes say a RR spike was placed on centerline of CSAH 23 and online with a tree line west for the assumed corner location.

2001 Westwood Professional Services, Inc. found a RR spike at the centerline of a north/south road and a tree line east/west.

2003 Westwood Professional Services, Inc. found RR spike. RR spike is 16.14 feet south and 6.79 feet west of the lost position. Measured 2711.91 feet to the NE corner and 2679.53 feet to the SE corner with a delta angle of 0-17' left, which compares reasonably well with the 1931 highway stationing.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 108278.960

E- 526910.208