

Statement of Evidence:

K233

The East Quarter Corner of Section 23, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Bur Oak	S 67 W	173 links
8" Elm	S 59 E	335 links

1940 County Engineer's Notebook No. 134 contains survey of CAR 40 running south to north on section line. Corner is shown as a spike set in road on line with fence west. Ties:

TP	E	22.8'
FP	SW	35.65'

Stationing gives distances of 2903.9 feet to the SE corner and 2702.10 feet to the NE corner.

2002 On April 30, 2002 Westwood Professional Services, Inc. found a cast iron monument at the intersection of 125th Avenue NE (running north and south) and a fence line from the west. Measured 2906.24 feet to the SE corner and 2696.80 feet to the NE corner. On May 13, 2002 Westwood Professional Services, Inc. dug with a backhoe down to the natural ground around the cast iron monument. We found many large fieldstones but no corner monument. We have no evidence of who set the cast iron monument, but accepted it as marking the obliterated corner position using the road and fence line as evidence. Position agrees reasonably well to the 1940 assumed location. We left the cast iron monument as found. Filed Certificate of Location as Document No. 286407.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-114052.78

E-537487.89