

Statement of Evidence:

K183

The East Quarter Corner of Section 18, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees:

6" Blk Oak	N 2 /12 E	359 links
6" Blk Oak	N 6 1/4 W	570 links

1933 County Engineer's Notebook No. 67 shows road survey by H. G. Elletson running from the east and ending at this corner. Corner is shown as a spike in center of road north and fence south with ties same as listed in County Surveyor's Record Book 1, page 119:

FP	SW	30.8
TP	NW	67.4

1966 County Highway Notebook No. 2, page, 13, shows I.P. at corner with a distance of 2675.0 feet to the NE corner.

1967 Ties in notebook 67 show iron found:

PP	SW	52.9'
2nd F. P.	S	35.85'

(Note: No Good – mile straight)

1994 William Lunser, LS 9394, found a 1/2" iron pipe and replaced it with a cast iron monument at the centerline of roads east/west/north. He filed a Certificate of Location (#234171). Doc. No. 234169 notes a distance of 5194.90 feet to the East 1/4 corner Sec 17.

2001 Westwood Professional Services, Inc. found a cast iron monument and located it using GPS. We measured a distance of 5195.12 feet to the East 1/4 corner Sec 17, 2674.52 feet to the NE corner, and 2676.48 feet to the SE corner. CIM is 11.7 feet east of a straight line between section corners.

2008 The County Surveyor's Office searched and found a cast iron monument at the intersection of the centerlines of gravel roads east-west (30th Street N.E.) and north (85th Ave. N.E.). Position agrees with 1966 distance to NE corner (2674.49 ft. vs. 2675.0 ft.) and 1967 tie to power pole. The Surveyor accepts the CIM position and set new ties.

County Coordinates Obtained by GPS (CIM)
NAD 83 (1996 Adjustment)
N-119052.821
E-516475.394

Benton County Surveyor's Office
Jason W. Oberg, Deputy County Surveyor
Minnesota License No. 45872