

**Statement of Evidence:**

**K163**

The East Quarter Corner of Section 16, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees:

12" W Oak	S 15 1/2 W	97 links
6" W Oak	N 24 1/2 E	46 links

Undated County Surveyor's Record Book 1, page 115, notes the corner at centerline of C.A.R. "H" opposite fence line east.

1931 County Engineer's Notebook No. 61 contains road survey that shows corner marked by a hub with road west and fence line east with ties:

Cor. F. P.	E	21.9'
F. P.	NE	26.0'

Stationing gives distances of 2626.4 feet to the NE corner and 2666.3 feet to the SE corner with a delta angle of 1-01' right (running north to south).

1933 County Engineer's Notebook No. 67 shows road survey by H. G. Elletson starting at this corner and running west. Corner is shown as a spike in center of road with fence east with ties:

F.P.	E	29.1'
P.P.	NE	38.7'

(Note says move corner 4 1/2 ' south?)

2001 Westwood Professional Services, Inc. found a PK at the centerline of roads north/south/west,

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-

E-