

**Statement of Evidence:**

**K063**

The East Quarter Corner of Section 6, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original General Land Office survey established this corner set a wood post at this location and bearing trees were recorded.

5" Iron wood	S 43 E	14 links
13" Blk Ash	S 80 W	33 links

1913? County Surveyor's Records, on pages 34 & 35, contains a survey of the west line of Section 5 by County Surveyor, J. A. Stanton, which notes this corner set lost with the following distances:

2602.50 feet to the NE corner Sec 6  
2611.50 feet to the SE corner Sec 6

2003 Barry Dorniden, LS23044, with Duffy Engineering, set corner in north-south road and occupation west. Measured 2556.87 feet to the NE corner and 2672.41 feet to the SE corner with an interior angle of 176-44-38.

County Coordinates furnished by Duffy:

NAD 83 (1996 Adjustment)  
N- 129632.663  
E- 516119.179

2004 Analysis of the corner set in 2003 shows that it is 74.25 feet east of a straight line between section corners. The lost position on a straight line is 61.98 feet south and 68.66 feet west of the corner set in 2003. The lost position distances would be 2616.2 feet to the SE corner and 2610.97 feet to the NE corner. Needs further field investigation, including searching for 1/16<sup>th</sup> corners along the section line north and south, which were set in 1913.

County Coordinates furnished by MN/DOT from GPS to ½" iron pipe:

NAD 83 (1996 Adjustment)  
N- 129632.435  
E- 516118.028

***POSITION IS QUESTIONABLE – NEEDS FURTHER REVIEW!***