

Statement of Evidence:

K364

Southeast Corner of Section 36, Township 36 North, Range 29 West, St. George Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as:
- | | | |
|------------|------------|-----------|
| 8" Bur Oak | N 70 1/2 E | 382 links |
| 8" Bur Oak | N 29 W | 438 links |
| 8" Bur Oak | S 52 W | 722 links |
- 1916 County Surveyor's Record Book 1, pages 67 to 69, and Record Book A, Map No. 29, contains a survey of Section 31, 36-28 by J. P. Soderstrum. He notes that he found all 3 Gov't BTs and set stake in road accordingly.
- 1940 County Engineer's Notebook No. 134 contains survey of CAR 40 running north from this corner on township line. Ties:
- | | | |
|--------|---|-------|
| 4" Oak | W | 35.9' |
|--------|---|-------|
- 1972 John Oliver, LS 8194, Sherburne County Surveyor, found old wooden stake at 40.1 feet from dead 8" Br. Oak. Resident Winkleman said corner was wooden stake. Brown's 1931 ties: 4" Br. Oak SW 44.2 feet is gone and 4" Br. Oak West 40.5 feet was found. He set a cast iron monument and filed Certificate of Location in Sherburne County (Doc. No. 121134).
- 1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:
- | |
|----------------|
| N- 100368.276 |
| E – 542834.596 |
- 1999 Sherburne County Surveyor's Office found CIM per Document No. 173043. New ties and Certificate of Location prepared.
County Coordinates converted from Sherburne County Coordinates:
NAD 83 (1986 Adjustment)
- | |
|--------------|
| N- 100368.12 |
| E- 542834.88 |
- 2005 County Coordinates obtained by GPS to CIM
NAD 83 (1996 Adjustment)
- | |
|---------------|
| N- 100368.409 |
| E- 542834.373 |