

**Statement of Evidence:**

**K362**

Northeast Corner of Section 36, Township 36 North, Range 29 West, St. George Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post with bearing trees noted as:  
10" Bur Oak S 17 1/2 E 1181 links  
8" Bur Oak N 56 E 491 links  
A line tree was noted as a 6" Bur Oak South 16.95 chains.

1916 County Surveyor's Record Book 1, pages 67 to 69, and Record Book A, Map No. 29, contains a survey of Section 31, 36-28 by J. P. Soderstrum. He states he located corner in center of north-south road from GLO BT to the SE – S 17 1/2 E 1188 links and planted a 5" x 5 " x 24 " granite stone for the corner.

1922 Bradley Engineering Services did a survey to establish the north-south 1/4 line of Section 31 filed in Plat Cabinet D, 95B. The survey shows stone used for the corner.

1940 County Engineer's Notebook No. 134 contains survey of CAR 40 running south to north on township line. Corner is shown as a granite monument. Ties:  
FP E 21.90  
FP SE 51.75

1964 County Surveyor's Record Book 1, page 155 contains ties to a granite monument:  
TP SE 50.8  
PP NW 72.5  
Other ties (No Date):  
FP East 25.9  
FP West 32.5  
(County Engineer's Notebook No. 134 shows hub set over granite monument with same ties.)

1983 David Regan, LS 12236, found a 5 1/2 " x 5 1/2 " granite stone monument in center line of north-south road. He set a 1/2 " iron pipe over the stone monument and filed a Certificate of Location (Doc. No. 166041).

2005 Westwood Professional Services, Inc. found 1" iron pipe in center of north-south road.

2008 The Benton County Surveyor's Office found a 1/2" open iron pipe in the center of a north-south bituminous road (Benton Co. Rd 49). Found a PP tie which checks with Regan's 1983 tie when he found the Soderstrum stone from 1916. The Surveyor accepts the position and set additional ties.

County Coordinates obtained by GPS:  
NAD 83 (1996 Adjustment)  
N- 105679.026  
E- 542844.045