

**Statement of Evidence:**

**M153**

East Quarter Corner of Section 15, Township 36 North, Range 31 West, Sauk Rapids Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post for this corner and bearing trees were recorded.

10" Black Oak	S 50 E	115 links
8" Black Oak	S 74 E	94 links

This corner is noted on the following recorded plats:

<i>DANIELS PARKVIEW FOUR</i>	<i>3/13/1996</i>	Paul E. Wellen
<i>EASTERN STAR ESTATES</i>	<i>2/14/1996</i>	Paul E. Wellen
<i>EASTERN STAR ESTATES PLAT 2</i>	<i>1/16/1997</i>	Linda H. Brown
<i>EASTERN STAR ESTATES PLAT 3</i>	<i>2/12/1999</i>	Paul E. Wellen
<i>DANIELS PARKVIEW (CIM)</i>	<i>6/25/1990</i>	Sidney Williamson
<i>DANIELS PARKVIEW THREE</i>	<i>10/9/1992</i>	Sidney Williamson
<i>OAKWOOD VILLAGE (CIM)</i>	<i>1/6/1994</i>	Paul E. Wellen

1981 William Lunser, LS 9394, set a cast iron monument at the corner using reference ties from others and filed a Certificate of Location (#173425). Notes distances of 2664.22 feet to the NE corner and 2663.59 feet to the SE corner.

1984 Paul Wellen, LS 10461, notes a cast iron monument at the corner and a distance of 2664.08 feet to the NE corner and 2663.58 feet to the SE corner Sec 15.

1991 James Nielsen, LS 11865, found a Benton County cast iron monument 1.5' west of the north/south centerline and two of Lunser's reference ties. A Certificate of Location (#216785) was filed. The monument is 0.23' south and 0.22' west of the lost position.

1993 MN/DOT Road Right of Way Plat 05-12 shows a CIM at corner.

2003 Corner has been destroyed by road construction.  
County Coordinates computed from MN/DOT information:  
NAD 83 (1996 Adjustment)  
N-118529.996  
E-468000.997

2008 Westwood Professional Services, Inc. found a PK nail at the corner location. Measured 2664.10 feet to the NE corner and 2663.61 feet to the SE corner of the section which agrees with 1981 Lunser and 1984 Wellen distances. PK is 0.38 feet SW of lost position and coordinates obtained by GPS coincide with 2003 MN/DOT information. PK nail is accepted as marking the obliterated position for this corner. PK was replaced with PK nail and Benton County Disk.