

Statement of Evidence:

M011

North Quarter Corner of Section 1, Township 36 North, Range 31 West, Sauk Rapids Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established this corner and set a wood post at this location and bearing trees were recorded.

10" Bur Oak	N 72 E	171 links
10" Bur Oak	N 49 W	173 links

Notes show corner at the edge of a brook. Line trees were noted as a 12" Poplar East 11.1 chains and a 4" Blk Oak West 22.62 chains.

1990 Paul E Wellen, LS 10461, found a 3/4" iron pipe near fence lines running east, south, and west. He set a cast iron monument over the 3/4" iron pipe and filed a Certificate of Location (#201564). The cast iron monument is 0.25 feet east of the fence corner. He measured 2676.34 feet to the NW corner and 2684.32 feet to the NE corner of Section 1.

2002 No resurvey information found on this corner in the Benton County records.

2004 Found CIM and measured 2676.21 feet to the NW corner and 2684.42 feet to the NE corner.
County Coordinates obtained by GPS to CIM:
NAD 83 (1996 Adjustment)
N- 132133.913
E- 475825.315

2011 The Benton County Surveyor's Office found the Cast Iron Monument (CIM) at the intersection of fences east-west and south and 225 feet west of a fence to the north. The CIM fits a split of distances between section corners within 4 feet and has been the accepted position since 1990. The 2004 coordinates were verified and reference ties established.