

Statement of Evidence:

M121

North Quarter Corner of Section 12, Township 36 North, Range 31 West, Sauk Rapids Township, 4th Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post for this location and bearing trees were recorded.
14" Aspen S 58 E 52 links

1985 William Lunser, LS 9394, set a cast iron monument at the intersection of a fence line north/south and on line between the NE and the NW Cor. of Section 12. He filed a Certificate of Location (#173422). He also notes the distance to the NW Corner of Sec. 12 is 2679.51 feet and the distance to the NE Corner of Sec. 12 is 2694.25 feet.

2002 No resurvey information was found on this corner in the Benton County records.

2004 County Coordinates from SEPI to CIM by traverse:
NAD 83 (1996 Adjustment)
N- 126534.425
E- 475904.180

2008 Westwood Professional Services, Inc. found a cast iron monument ~3 feet south of the centerline of the township road and in line with fence lines north and south. CIM fits 1985 Lunser ties and we measured 2679.55 feet to the NW corner and 2694.29 feet to the NE corner which agrees with Lunser measurements. CIM is accepted as marking the obliterated position for this corner.
County Coordinates obtained by GPS coincide with 2004 SEPI position.