

**Statement of Evidence:**

**M092**

Northeast Corner of Section 9, Township 36 North, Range 31 West, Sauk Rapids Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey established this corner and set a wood post at this location and bearing trees were recorded.  
14" Burr Oak                    N 45 W 19 links  
8" Blk Oak                    S 60 W 61 links

This corner is noted on the following recorded plats:

<i>CZECH ADDITION</i>	8/6/1975	Paul E. Wellen
<i>CZECH ADDITION PLAT 2</i>	8/13/1962	Milner W. Carley
<i>RANCH ACRES ESTATE</i>	2/13/1961	M.B. Lang
<i>THOUSAND OAKS</i>	9/20/1983	Paul E. Wellen
<i>THE TOWNSITE OF SARTELL</i>	5/24/1906	Samuel S Chute

Undated                    MN/DOT road alignment for (old) TH 10 (Roll B-9) notes the corner is 981.1 feet from centerline.

1946                    MN/DOT road alignment for TH 10 (Roll D-8) notes the corner is at the intersection of roads east/west and a fence line north/south. The corner is 1030.0 feet from centerline.

1968                    County Highway: An iron pin was found at the corner location.

1974                    County Highway: a cast iron monument was set at the location of a found iron pipe.

1975                    M.W. Carley shows an iron at this corner.

1982                    David Regan, LS 12236, found a 3/8" iron pipe in the centerline of an east/west road. He set a cast iron monument. A Certificate of Location (#163375) was filed.

1995                    Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:  
N- 126581.387  
E- 462571.035

2003                    County Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 126581.479  
E- 462570.473

2008                    The County Surveyor's Office searched and found a cast iron monument at the centerline of an east-west road (Scenic Drive). All four tie distances reported by Regan in 1982 agree well. The position gives a distance to the East 1/4 Cor. of 2749.61 feet. Surveyor accepts CIM and updated ties.

County Coordinates Obtained by GPS to CIM  
NAD 83 (1996 Adjustment)  
N- 126581.536  
E- 462570.484