

Statement of Evidence:

M112

Northeast Corner of Section 11, Township 36 North, Range 31 West, Sauk Rapids Township, 4th Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey established this corner and set a wood post at this location and bearing trees were recorded.

8" Aspen	N 62 W 187 links
8" Aspen	S 89 W 205 links

1984 On May 21, 1984 William Lunser, LS 9394, found a 6"X6" granite monument in intersection of roads north, south, and east.. He set a cast iron monument at the corner location and filed a Certificate of Location (#173423), which shows distance to the North 1/4 Corner of Section 12 is 2679.51 feet and the distance to the East 1/4 Corner of Section 11 is 2658.08 feet.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 126500.078
E- 473225.470

2002 No resurvey information was found on this corner in the Benton County records.

2003 Westwood Professional Services, Inc. found a cast iron monument at the corner and located it using GPS.

County Coordinates obtained by GPS (Cast Iron Monument)
NAD 83 (1996 Adjustment)
N-126500.271
E-473224.850

2008 The County Surveyor's Office searched and found a cast iron monument at the intersection of a north-south road (County Road No. 57) and an east gravel road (45th Street N.E.). The position gives a distance to the East 1/4 Cor. of 2658.11 feet and a distance to the North 1/4 Cor. of Sec. 12 of 2679.54 feet with a deflection angle of 89-36-17 left (south to north), which agrees well with Lunser's 1984 report. Surveyor accepts CIM and set a PK nail with a Benton County Surveyor disk over the monument and updated ties.

County Coordinates obtained by GPS (PK nail)
NAD 83 (1996 Adjustment)
N-126500.182
E-473224.861