

Statement of Evidence:

M365

The South Quarter Corner of Section 36, Township 36 North, Range 31 West, Sauk Rapids Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded

24" Bur Oak	S 38 E	325 links
10" Bur Oak	S 4 3/4 W	472 links

Line trees are noted as a 12" Bur Oak West 12.50 chains and a 10" Bur Oak East 20.59 chains.

This corner is noted on the following recorded plats:

CENTER EAST (1" IP over STONE)	8/22/1992	Sidney Williamson
LINCOLN PLACE ADDITION (1" IRON over STONE)	4/16/1985	William Lunser
AUDITORS 1916 SUBDIVISION	4/18/1916	J.P. Soderstrum
WOODCRAFT INDUSTRIES (1" IM)	10/26/1988	David Regan
AA WRIGHT'S ADD'N TO ST. CLOUD	8/8/1914	C.H. West
ALLEN ADDITION	11/8/1974	Delbert Reike

Undated Roll B-09 of the MnDOT road alignment plans a distance of 995.02 feet to centerline and a distance of 414.0 feet to centerline.

1993 Sherburne County Surveyor, Daniel Nichols, LS 19839, found a $\frac{3}{4}$ " iron pipe that has been used over the years by Lunser, LS 9394, Regan, LS 12236, and Wellen, LS 10461, as the $\frac{1}{4}$ corner. Set CIM and filed Certificate of Location in Sherburne County.

1998 Sherburne County Surveyor's Office found CIM and updated ties.

2000 Certificate of Location filed in Sherburne County by James Kramer, LS 23668, shows found CIM.

County Coordinates converted from Sherburne County Coordinates

NAD83 (1986 Adjustment)
N – 100007.19
E – 476395.55

2003 County Coordinates Obtained by GPS to CIM:
NAD 83 (1996 Adjustment)
N- 100007.400
E- 476395.060