

Statement of Evidence:

G033

East Quarter Corner of Section 3, Township 37 North, Range 30 West, 4th Principal Meridian, (Mayhew Lake Township) Benton County, Minnesota.

1852 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as:

12" Aspen	N 65 1/2 W	12 links
12" Aspen	S 65 1/2 E	14 links

1938 County Engineer's Notebook No. 122 contains a road survey for CAR 24 running north to south. Notes do not show this corner with a distance of 5617.1 feet for the east line of Section 3.

Un-dated: County Engineer, H. G. Elletson shows spike at corner with ties:

14" Oak	SE	41.3
FP	E	20.0

2002 Westwood Professional Services, Inc. found a cast iron monument (CIM) in the center of north-south road and in line with field line west and fence line east. Origin of CIM is not known. No evidence of Elletson's ties remain. Left CIM as found and took ties.

2008 Westwood Professional Services, Inc. found a cast iron monument (CIM) in the center of north-south road and in line with field line west and fence line east. Origin of CIM is not known. The distance to the SE corner measures 2676.10, fitting the GLO distance within three (3) feet taking into account one (1) extra tally. The distance to the NE corner measures 2941.99, being 153.49 feet long of GLO distance. Several closing distances vary from GLO distance in excess of 100 feet in Benton County for unknown reasons. The CIM was accepted as the best available evidence of the corner position.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 161464.602
E- 500396.925

2010 The Benton County Surveyor's Office found the CIM as noted in 2008. Mr. Elletson's ties were searched for and not found. The 2008 coordinates were verified and reference ties were established as shown.