

Statement of Evidence:

G133

East Quarter Corner of Section 13, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1849 Corner established by Original US General Land Office survey and marked by a wood post with bearing trees noted as.

6" Ironwood	S 22 E	27 links
18" W Oak	N 54 W	39 links

Line trees were noted as a 18" Elm, South, 19.80 chains and a 6" Poplar, North, 19.63 chains.

1994 David Regan, LS 12236, found a 1/2" iron pin on the centerline of road north/south and a fence line west and +/- 28 feet south of a field line east. He filed a Certificate of Location (#231243).

2008 Westwood Professional Services found a 1/2" iron pin on the centerline of road north/south, 8 feet south of a fence line west and +/- 29 feet south of a fence line east. The found pin fits occupation lines at the sixteenth north within a foot and south within 3 feet and fits a split of the distances between section corners within 3.5 feet. The iron pin is accepted as marking the obliterated corner position.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 150815.653
E- 510819.970

2010 The Benton County Surveyor's Office found the 1/2" iron pin 0.3 feet below the road surface, established references as shown and verified the 2008 coordinates.