

Statement of Evidence:

G153

East Quarter Corner of Section 15, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1852 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as:

8" Ash	N 59 W	12 links
30" Bur Oak	S 14 E	21 links

1938 County Engineer's Notebook No. 122 contains a road survey for CAR 24 running north to south. Notes show corner marked by a spike set in road with fence west. Ties:

10" Elm	SW	42.9'
14" Elm	W	47.5'

Stationing gives distances of 2689.4 feet to the NE corner and 2713.7 feet to the SE corner.

1992 Paul Wellen, LS 10461, set a cast iron monument at the intersection of the centerline of County Road 59 (running north and south) and a fence line (west) and a field line (east). He filed a Certificate of Location (#216297).

2008 Westwood Professional Services found a cast iron monument at the intersection of the centerline of County Road 59 (running north and south) and a fence line (west) and a field line (east).

Coordinates Obtained by GPS NAD 83 (1996 Adjustment)

N- 150844.612

E- 500300.556

2008 The County Surveyor's Office found a cast iron monument at the intersection of the centerline of County Road 59 (running north and south) and a fence line (west) and a field line (east). Stationing gives distances of 2687.77 ft. to the NE corner and 2714.38 ft. to the SE corner which agree reasonably well with the County Engineer's 1938 distances. The Surveyor was able to locate two of Wellen's 1992 ties to the P.P. to the NW and the F.P. to the SW, however the F.P. to the W. was destroyed. The Surveyor accepts the cast iron monument and set ties to same.

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 150844.715

E- 500300.600