

**Statement of Evidence:**

**G163**

East Quarter Corner of Section 16, Township 37 North, Range 30 West, 4<sup>th</sup> Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

- 1852 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as:

7" Bur Oak                    S 19 E                    136 links

- 1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 150856.086  
E - 495012.949

- 2002 No resurvey information was found on this corner in the Benton County records.

- 2008 Westwood Professional Services found a cast iron monument.

Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 150856.255  
E- 495012.436

- 2008 The County Surveyor's Office found a cast iron monument in centerline of north-south gravel road (45<sup>th</sup> Ave NE) and a tree line (west). The Surveyor notes distances of 2650.95 ft. to the NE corner and 2670.37 ft. to the SE corner. The coordinates agree with those obtained in 1995 by Comstock and Davis and those in 2008 by Westwood Professional Services. The Surveyor accepts the cast iron monument and set ties to same.

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 150856.332

E- 495012.410