

Statement of Evidence:

G183

East Quarter Corner of Section 18, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1852 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as.

8" Blk Oak	N 6 1/2 E	326 links
12" Aspen	S 1 1/4 E	1417 links

1939 County Engineer's Notebook No. 158 contains road survey for CAR No. 20 running east and west. Notes state a hub set on section line with ties:

PP	S	33.7'
TP	NW	71.8'

Notes give distance of 1317.6 feet west to an iron pipe at the 1/16th corner.

1979 Paul Wellen, LS 10461, set a cast iron monument at the centerline of a road east/west and a driveway north. He filed a Certificate of Location (Doc. No. 154385) and notes a distance of 2639.11 feet to the center of Sec 18.

2001 Westwood Professional Services, Inc. found a cast iron monument at the centerline of a road east/west and a driveway north.

Coordinates Obtained by Traverse

NAD 83 (1996 Adjustment)

N- 150843.992

E- 484368.095

2008 The County Surveyor's Office searched and found Wellen's 1979 cast iron monument. Said monument lies 2668.91 ft. south of the NE Cor. and 2673.19 ft. north of the SE Cor. Position falls along the centerline of an east-west road (County Road 43) and west of the driveway to the north. The iron pipe marking the 1/16th corner as referenced in the 1939 County Engineer's Notebood was not found. The Surveyor accepts the position as marking the best evidence and updated ties. Coordinates obtained by GPS agree with those reported by Westwood Professional Services, Inc. in 2001, above.

2009 The Benton County Surveyor's Office found a PK Nail with Benton County washer set over the cast iron monument.