

Statement of Evidence:

G263

East Quarter Corner of Section 26, Township 37 North, Range 30 West, Mayhew Lake Township, 4th Principal Meridian, Benton County, Minnesota.

- 1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.
- | | | |
|---------|--------|----------|
| 16" Elm | N 32 W | 33 links |
| 12" Elm | N 72 E | 43 links |
- 1941 County Engineer's Notebook No. 150 contains a road survey for CAR 25 running south to north on section line. Corner is shown marked by a spike set in center of road with town road west and fence line east. Ties:
- | | | |
|----|----|-------|
| FP | E | 25.7' |
| FP | SE | 31.7' |
- Stationing gives distances of 2628.2 feet to the SE corner and 2617.0 feet to the NE corner with a delta angle of 0-05' right.
- 1944 County Engineer's Notebook No. 164 contains a road survey for CAR 25 running south to north on section line. Corner is shown marked by a hub set in center of road with town road west and fence line east. Ties:
- | | | |
|------------|----|-------|
| 18" W. Oak | NE | 68.5' |
| 15" W. Oak | E | 70.3' |
- Stationing gives distances of 2627.3 feet to the SE corner and 2618.8 feet to the NE corner with a delta angle of 0-07' right.
- 1969 County Engineer's Notebook No. 288 contains a road survey for CSAH No. 25 running south to north on section line. Corner is shown marked by a nail set in center of road with town road west and fence east. Ties:
- | | | |
|---------|----|-------|
| TP | SE | 49.85 |
| 18" Elm | NE | 49.4 |
- Stationing gives distances of 2629.7 feet to the SE corner and 2616.2 feet to the NE corner with a delta angle of 0-06 1/2' right.
- 1990 Paul Wellen, LS 10461, set a cast iron monument at the intersection of the centerlines of roads north/south/west. He filed a Certificate of Location (#200724).
- 2002 County Coordinates Obtained by GPS to CIM
NAD 83 (1996 Adjustment)
N- 140116.377
E- 505355.223